

# ADVANCED MACHINING TOWARDS IMPROVED MACHINABILITY OF DIFFICULT-TO-CUT MATERIALS

---

Edited by:

A.K.M. Nurul Amin (Chief Editor)

Dr. Erry Yulian Triblas Adesta

Dr. Mohammad Yeakub Ali



IIUM PRESS

INTERNATIONAL ISLAMIC UNIVERSITY MALAYSIA

**ADVANCED MACHINING**  
**TOWARDS IMPROVED MACHINABILITY OF**  
**DIFFICULT-TO-CUT MATERIALS**

*Edited by:*  
*A.K.M. Nurul Amin (Chief Editor)*  
*Dr. Erry Yulian Triblas Adesta*  
*Dr. Mohammad Yeakub Ali*



**IIUM Press**

Published by:  
IIUM Press  
International Islamic University Malaysia

First Edition, 2011  
©IIUM Press, IIUM

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without any prior written permission of the publisher.

Perpustakaan Negara Malaysia

Cataloguing-in-Publication Data

Advanced Machining Towards Improved Machinability of Difficult-To-Cut Materials: A.K.M.  
Nurul Amin, Erry Yulian Triblas Adesta & Mohammad Yeakub Ali

ISBN: 978-967-418-175-8

Member of Majlis Penerbitan Ilmiah Malaysia – MAPIM  
(Malaysian Scholarly Publishing Council)

Printed by :  
**IIUM PRINTING SDN.BHD.**  
No. 1, Jalan Industri Batu Caves 1/3  
Taman Perindustrian Batu Caves  
Batu Caves Centre Point  
68100 Batu Caves  
Selangor Darul Ehsan  
Tel: +603-6188 1542 / 44 / 45 Fax: +603-6188 1543  
EMAIL: iiumprinting@yahoo.com

<b>SECTION A: HEAT ASSISTED MACHINING</b>	<b>1</b>
1. CHAPTER 1: INFLUENCE OF WORKPIECE PREHEATING ON CHATTER AND MACHINABILITY OF TITANIUM LOY - TI6AL4V	1
2. CHAPTER 2: MACHINABILITY IMPROVEMENT IN END OF MILLING TITANIUM ALLOY TI-6AL-4V THROUGH PREHEATING	9
3. CHAPTER 3: SOME ASPECTS OF IMPROVED MACHINABILITY IN PREHEATED MACHINING OF TITANIUM ALLOY TI-6AL-4V	19
4. CHAPTER 4: MACHINABILITY ASPECTS IN HEAT ASSISTED MACHINING OF HARDENED STEEL AISI H13 USING COATED CARBIDE TOOL	27
5. CHAPTER 5: TOOL WEAR AND SURFACE ROUGHNESS ASPECTS IN HEAT ASSISTED END MILLING OF AISI D2 HARDENED STEEL	35
6. CHAPTER 6: MODELING IN PREHEATED MACHINING OF AISI D2 HARDENED STEEL	43
7. CHAPTER 7: RELATIVE PERFORMANCES OF PREHEATING, CRYOGENIC COOLING AND HYBRID TURNING OF STAINLESS STEEL AISI 304	49
<b>SECTION B: CHATTER AND SELECTED METHODS OF CHATTER SUPPRESSION</b>	<b>57</b>
8. CHAPTER 8: ROLE OF THE FREQUENCY OF SECONDARY SERRATED TEETH IN CHATTER FORMATION DURING TURNING OF CARBON STEEL AISI 1040 AND STAINLESS STEEL	57
9. CHAPTER 9: INFLUENCE OF THE ELASTIC SYSTEM AND CUTTING PARAMETERS ON CHATTER DURING MACHINING OF MILD STEEL	65
10. CHAPTER 10: INFLUENCE OF CHATTER ON TOOL LIFE DURING END MILLING OF ALUMINIUM AND ALUMINIUM ALLOY ON VMC	75

<b>11</b>	<b>CHAPTER 11: A NEW METHOD FOR CHATTER SUPPRESSION AND IMPROVEMENT OF SURFACE ROUGHNESS IN END MILLING OF MILD STEEL</b>	<b>83</b>
<b>12</b>	<b>CHAPTER 12: APPLICATION OF PERMANENT ELECTROMAGNET FOR CHATTER CONTROL IN END MILLING OF MEDIUM CARBON STEEL</b>	<b>91</b>
<b>13</b>	<b>CHAPTER 13: APPLICATION OF PERMANENT ELECTROMAGNET FOR CHATTER CONTROL IN END MILLING OF TITANIUM ALLOY - Ti6Al4V</b>	<b>99</b>
<b>14</b>	<b>CHAPTER 14: CHATTER SUPPRESSION IN END MILLING OF TITANIUM ALLOY Ti6Al4V APPLYING PERMANENT MAGNET CLAMPED ADJACENT TO THE WORKPIECE</b>	<b>107</b>
	<b>SECTION C: MODELING AND OPTIMIZATION IN MACHINING</b>	<b>117</b>
<b>15</b>	<b>CHAPTER 15: A COUPLED ARTIFICIAL NEURAL NETWORK AND RSM MODEL FOR THE PREDICTION OF CHIP SERRATION FREQUENCY IN END MILLING OF INCONEL 718</b>	<b>117</b>
<b>16</b>	<b>CHAPTER 16: APPLICATION OF RESPONSE SURFACE METHODOLOGY COUPLED WITH GENETIC ALGORITHM FOR SURFACE ROUGHNESS OF INCONEL 718</b>	<b>123</b>
<b>17</b>	<b>CHAPTER 17: DEVELOPMENT OF A MATHEMATICAL MODEL FOR THE PREDICTION OF SURFACE ROUGHNESS IN END MILLING OF STAINLESS STEEL SS 304</b>	<b>133</b>
<b>18</b>	<b>CHAPTER 18: DEVELOPMENT OF AN ARTIFICIAL NEURAL NETWORK ALGORITHM FOR PREDICTING THE CUTTING FORCE IN END MILLING OF INCONEL 718 ALLOY</b>	<b>143</b>
<b>19</b>	<b>CHAPTER 19: DEVELOPMENT OF AN ARTIFICIAL NEURAL NETWORK ALGORITHM FOR PREDICTING THE SURFACE</b>	<b>149</b>
<b>20</b>	<b>CHAPTER 20: DEVELOPMENT OF TOOL LIFE PREDICTION MODEL OF TiAlN COATED TOOLS DURING PART C: HIGH SPEED HARD MILLING OF AISI H13 STEEL</b>	<b>155</b>
<b>21</b>	<b>CHAPTER 21: MODELING FOR SURFACE ROUGHNESS IN END-MILLING OF TITANIUM ALLOY Ti-6Al-4V USING UNCOATED WC INSERTS</b>	<b>161</b>

22	CHAPTER 22: MODELING OF SURFACE ROUGHNESS DURING END MILLING OF AISI H13 HARDENED TOOL STEEL	167
23	CHAPTER 23: MODELING OF TOOL LIFE USING RESPONSE SURFACE METHODOLOGY IN HARD MILLING OF AISI D2 TOOL STEEL	175
24	CHAPTER 24: OPTIMIZATION OF SURFACE ROUGHNESS IN HIGH SPEED END MILLING OF TITANIUM ALLOY Ti-6Al-4V UNDER DRY CONDITION	181
25	CHAPTER 25: COMPARISON OF SURFACE ROUGHNESS IN END-MILLING OF TITANIUM ALLOY Ti-6Al-4V USING UNCOATED WC-CO AND PCD INSERTS THROUGH GENERATION OF MODELS	189
26	CHAPTER 26: ASSESSMENT OF PERFORMANCE OF UNCOATED AND COATED CARBIDE INSERTS IN END MILLING OF Ti-6Al-4V THROUGH MODELLING	195
	SECTION D: CRYOGENIC AND HIGH SPEED MACHINING OF METALS AND NON METALS	203
27	CHAPTER 27: THE EFFECT OF CRYOGENIC COOLING ON MACHINABILITY OF STAINLESS STEEL DURING TURNING	203
28	CHAPTER 28: COMPARISON OF MACHINABILITY OF CERAMIC INSERT IN ROOM TEMPERATURE AND CRYOGENIC COOLING CONDITIONS DURING END MILLING INCONEL 718	209
29	CHAPTER 29: HIGH SPEED END MILLING OF SINGLE CRYSTAL SILICON SING DIAMOND COATED TOOL	217
30	CHAPTER 30: IMPLEMENTATION OF HIGH SPEED OF SILICON USING DIAMOND COATED TOOLS WITH AIR BLOWING	225
31	CHAPTER 31: ELIMINATION OF BURR FORMATION DURING END MILLING OF POLYMETHYL METHACRYLATE (PMMA) THROUGH HIGH SPEED MACHINING	233
32	CHAPTER 32: WEAR MECHANISMS IN END MILLING OF INCONEL 718	239

33	CHAPTER 33: PERFORMANCE OF UNCOATED WC-CO INSERTS IN END MILLING OF ALUMINUM SILICON CARBIDE (ALSiC)	247
34	CHAPTER 34: APPLICATION OF PCD INSERTS IN END MILLING OF ALUMINUM SILICON CARBIDE (ALSIC)	253
35	CHAPTER 35: EFFECTS OF SCRIBING WHEEL DIMENSIONS ON LCD GLASS CUTTING	259

## Chapter 16

# **Application of Response Surface Methodology Coupled with Genetic Algorithm in the Optimization of Cutting Conditions for Surface Roughness in End-Milling of Inconel 718 Using Coated WC-Co Inserts**

M. H. Ishtiyag<sup>1</sup>, A.K.M. Nurul Amin<sup>2</sup>, M. Anayet U. Patwari<sup>3</sup>  
<sup>1,2,3</sup>Faculty of Engineering- International Islamic University Malaysia

e-mail address of the corresponding author: *akamin@iium.edu.my*

### 1.0 INTRODUCTION

Process modeling and optimization are two important issues in today's manufacturing. It is important, in metal cutting, to select the machining parameters to ensure high quality of machining products, reduce machining costs and increase machining efficiency. Nowadays surface roughness and accuracy of product is getting greater attention in the industry. Surface roughness and dimensional accuracy have important bearing on performances of any machined part. Therefore, there is a need for predictions of these values. However number of surface roughness prediction models available in the literature is limited [1-5]. B. Ozcelik et al [2] generated 81 experimental data to develop a model by using Artificial Neural Networking (ANN) for predicting the surface finish of Inconel 718 in End Milling and then used the developed ANN model as a fitness function of GA to optimize the surface roughness. But the development of surface roughness prediction model increases the total number of tests and as a result the experimentation cost also increases.

Response Surface Methodology (RSM), as a group of mathematical and statistical techniques, is useful for modeling the relationship between the input parameters (cutting conditions) and the output variables. Many machining researchers have used response surface methodology to design their experiments and assess results. Alauddin et al [3] applied response surface methodology to predict the surface finish in end milling of Inconel 718 considering cutting speed and feed as input parameters. S. Sharif et al [4] developed a predicted model for surface roughness when end milling titanium alloy (Ti-6Al-4V) using uncoated carbide under flooded condition.

In the present work, an effort has been made to estimate the surface roughness values in end milling of Inconel 718 using RSM. It has also been attempted to optimize the surface roughness prediction model using a GA approach.